


SPECIFICATION SHEET FREEDOM RM

Roof Top Mount Box Awning


- Compact design.
- > Lightest weight roof mounted box awning.
- > Self-contained, mounts using concealed mounting brackets.
- Mounting brackets available for most applications.
- > Fully retractable and self storing.
- > Lateral spring arm design.
- > Ground support arms store inside the lead rail and are easy to access.
- Can use the Buena Vista room for added living space.





Easy to use manual crank operation with positive crank lock when closed:


Also available as 12V motorized;



SPECIFICATIONS

Widths:	meters	2.44		.57	3	3.5	4	
	inches	96	101		118	138	157	
Extension:		180cm (72")	200cm (80")		250cm (98")			
LEADING EDGE POSITION ACTUATION AND CONTROL								
Power:		Lateral Arm Spring			Minimum Tension Open			
Position Control:		Motorized: Roll Out/In Controlled by Electrical Motor						
		Manual: Roll		Roll Out/	Out/In Controlled by Manual Crank (crank ratio = 2.7:1)			
Note: 4.5 meter and 5 meter awnings are only available in the motorized configuration.						on.		
MOTOR SPECIFICATIONS								
Motor Type:		Tubular						
Power:		12VDC Minimum: 10VDC Output: 30 Watts						
		Nominal Current: 2.5Amps			Max Curre	Max Current: 14Amps (stall @ min voltage)		
Power Sou	ower Source: Motor and switch is routed and hardwired into the vehicle's 12V system						em	
Torque	rque Continuous: 6Nm/4.5 ft-lbs.			os.	Tightening: 18Nm/13.2 ft-lbs.			
Speed		15 rpm						
COLORS AVAILABLE								
Case		Satin, White or Black						
Fabric:1		Vinyl or Woven Acrylic						

FREEDOM RM



MEASURING AND INSTALLATION TIPS:

- For manual awning, actual measurement is 2" smaller than stated size; for motorized version, actual measurement is 2.69" smaller than stated size.
- Awning is mounted using concealed brackets.
- Mounting brackets available for some applications.
- The awning must be mounted into the vehicle structure to provide adequate support.
- Two bracket kits are available. For 4m and smaller, the sprinter bracket kit includes hardware to attach to the sprinter roof channel. The 2nd kit are brackets used for flat roof applications.
- For detailed information, refer to the installation and operations manuals.
- Maximum leg extension is 97".

ORDERING:

You will need to know the following information:

- Length of awning. Length measurement is the actual length of the case including end caps.
- Canopy color.
- · Case color.
- Manual or 12V motorized.
- Type of Bracket
- All orders are custom and Non-Returnable.

SHIPPING:

Cannot be shipped UPS. Applicable freight charges apply.

WARRANTY

The Freedom RM Patio Awning is covered by the standard Carefree of Colorado 1 year Limited Warranty.

ON-LINE AT WWW.CAREFREEOFCOLORADO.COM

♦ Product Manuals
♦ Fabric Options
♦ Warranty Information